

BETA MULTI-FLOW

FILTER CARTRIDGES
NOMINAL - STRING
WOUND OD 2.5"
64 MM

BÈTA

industrie



Agnim apitiusae nimilibus nest, to explicab ius que officipis adignihil iunt, quiae nulliqui accuptati niminit ape exeritatur simus doloreriam, sed que opta con cullat explaut empores ecaest atiorep tatatis nobis etustotate nam estibus mi, con reped ut volorio illenim inulpa ellabor ehenditati odit lam ne et lis iunt exeresto blam evenihiciae

FEATURES & BENEFITS

- SINGLE PASS EFFICIENCY: 99% UP
- HIGH FLOW RATE AND HIGH CAPACITY
- HIGH CAPACITY MAX: 18 KG/PCS
- HUGE FILTER SURFACE: 20 M²/PCS
- MATERIAL: 100% POLYPROPYLENE
- PRODUCED IN CLEAN ROOM

APPLICATIONS

AMINES

ACIDS AND BASES

BEER AND WINE

CARBON BEDS

COMPLETION FLUIDS

DEEP WELLS

DESALINATION

DI RESINS

EDIBLE OILS

EDM FLUIDS

FRUCTOSE

GLYCOL

GROUNDWATER CLEAN-UP

MACHINE COOLANTS

WASTEWATER

BÈTA INDUSTRIE SPECIALIST IN PROCESS SPECIFIC APPLICATIONS

BETA MULTI-FLOW

FILTER CARTRIDGES
NOMINAL - STRING
WOUND OD 2.5"
64 MM

BÈTA
industrie

TECHNICAL DATA

WORKING TEMPERATURE
Max. 80°C

DIFFERENCE PRESSURE
60 PSI at 86°F (30°C)

FLOW RATE
Max. 22 m³/hour

LENGTH/O-RING
40 inch / 226 O-ring

LENGTH
10", 20", 30", 40", 60"

MICRON RATINGS
(Single pass 99% efficiency):
1 up to 100 micron

CONSTRUCTION MATERIAL
- Polypropylene



ORDERING INFORMATION

	<i>Length</i>	<i>Micron rating</i>	<i>O-ring</i>	<i>End caps</i>
BETA BCMF	1	05	E	6
	1 - 10 inch 2 - 20 inch 3 - 30 inch 4 - 40 inch 6 - 60 inch	01 - 1 micron 02 - 2 micron 05 - 5 micron 10 - 10 micron 25 - 25 micron 50 - 50 micron 75 - 75 micron 100 - 100 micron	E - EPDM N - Buna N S - Silicone V - Viton	6 - 226/Flat